

1. Application

KOMFORTEX® Edge and Corner Profile are used as edging for indoor stables, outdoor stalls and pens, washing bays and paddocks on drainable surfaces concrete or asphalt. Their beveled edges facilitate access with wheelchairs and reduce the danger of stumbling at the edge of the surface.

KOMFORTEX® Edge and Corner Profile are manufactured by an environment friendly process and can be recycled as process raw material at the end of their service life.

2. Material

Rubber granulate: granulated recycled rubber
Binding agent: MDI polyurethane

3. Characteristics

Colour: red, green, grey or black (minor colour variations possible).
Surface: smooth with open pores, beveled edges

4. Dimensions / Tolerances

L x W x T, Weights:

Edge Profile: 1000 x 250 x 40/10 mm approx. 6,2 kg
Corner Profile: 1000 x 250 x 40/10 mm approx. 6,5 kg
Dimensional tolerances: +/- 0,8 %

5. Product testing

Chemical resistance: conditionally resistant to acids and bases
Cold fracture resistance: 24h / -40°C, no fracture
Cold crack resistance: 5h / -30°C, no cracks
Production facility inspection

6. Installation

Clean the existing paved substructure and be certain it is dry and level.
Securely cement KOMFORTEX® Edge and Corner Profile onto the substructure using dabs of 1-component PU adhesive cement.
Cement the joints between the slabs together with adhesive cement.
Note the complete installation instruction.